



8CH PoE 5MP H.265 NVR

Features

- 8-channel recording up to 5MP
- H.265, H.264 dual-stream recording
- 8 PoE ports dedicated for IP camera connection
- Sophisticated event management
- DDNS, P2P for Internet connectivity
- Embedded Linux ensuring reliable operations



Dimensions



Specifications

Model	NW-21108
VIDEO	
Compatibility	WAMA & ONVIF (Profile S) IP cameras
Input	8 dedicated PoE ports (IEEE 802.3af)
Resolution	2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576
Output	1 x HDMI (up to 1920x1080) 1 x VGA (up to 1920x1080)
Compression	H.265 / H.264 / MJPEG
Bit Rate	16kbps – 8000kbps
Display	1/4/6/8/9
AUDIO	
Input	IPC audio in
Output	1
Compression	G.711u
RECORDING AND PLAYBACK	
Max. Frame Rate	25/30fps
HDD	1 x 3.5" SATA
Recording Mode	Manual, event driven, schedule
Simultaneous Playback	4 channels
Searching Mode	Advanced timeline, channel, event, past moment
Playback Mode	Normal, fast FWD/BWD, slow FWD/BWD, 30-sec step, frame-by-frame
Snapshot	JPEG format
Back-up	Network, USB
EVENT	
Event Type	External alarm, video motion detection, video analytic (with intelligent IP cameras)
Video Analytic Function	-
Video Analytic Channel	-
Action Type	Dial-back, email notification, buzzer
External Alarm Input	-
Relay Output	-
COMMUNICATION	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, HTTP, HTTPS, DDNS, SMTP (SSL), DHCP, PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	4
MISCELLANEOUS	
Operating Environment	-10°C ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC48V, 10W (excluding HDD, IPC)
Dimension (mm)	320 (W) x 250 (D) x 50 (H)
Weight	1.2kg (excluding HDD)



WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,
608 Castle Peak Road, Kowloon, Hong Kong.

Tel : (852) 3703 9260

Email : info@wamatech.co

Fax : (852) 3705 0053

Website : www.wamatech.co